Health and Safety Plan for **McDonnell Douglas RFI** Hazelwood, Missouri Facility Volume III, Appendix B

Prepared for: McDonnell Douglas Aerospace St. Louis, Missouri

Prepared by: Environmental Science & Engineering, Inc. St. Louis, Missouri

May 29, 1997

ESE Project No. 5197-042-0100





RCRA Records Center

RECEIVED

ENVIRONMENTAL SCIENCE & ENGINEERING, INC.

JUN 3 1997

HASP APPROVAL

RCRA PERMITTING A COMPLIANCE BRANCH (RPCB) 8:00 am Scheduled Start-up Time: Scheduled Start-up Date: August, 1997 McDonnell Douglas Site: McDonnell Douglas RFI Project: Hazelwood, MO Project Number: Site Location: Facility 5197042 We have reviewed the attached HASP, including the Project Information Sheet, for the above referenced site. We recognize that when this form is completed, the attached HASP is approved for the field activities on the above referenced site. Changes to this HASP shall be documented in writing and approved. Name and Signature of HASP Author Name and Signature of HASP Reviewer 5/28/97 Project Manager Signature Date Field Implementation Manager Signature Site Health & Safety Officer Signature

HASP ACKNOWLEDGEMENT

Project:	McDonnell Douglas RFI	Site:	McDonnell Douglas
Project Number:	5197042	Site Location:	Hazelwood, MO Facility
limitations specified regarding the HAS	I understand the requirements of this id herein. I also acknowledge that I have an arrow at the prior all surveillance requirements applicable on-site activities.	we been given ar to performing fi	opportunity to have my questions eld activities. Health and safety
	Signature	Employee Nun	nber Date
		2	
9			
requirements for the surveillance require	I have verified that the employees list his site. I have also verified that the a ements and any client requirements to not have any medical restrictions that	bove employees l participate in a s	have fulfilled the medical ubstance abuse screening program
Project Manager's	Signature:		Date:

Table of Contents

Sect	ion		Page
1.0	Introdu	uction	. 1-1
	1.1	Site Information	. 1-1
	1.2	Objective	. 1-1
	1.3	Regulatory Requirements	. 1-1
2.0	ESE H	ealth and Safety Personnel	. 2-1
	2.1	Site Health and Safety Officer (SHSO)	. 2-1
	2.2	Local Health and Safety Representative (LHSR)	. 2-1
	2.3	ESE Regional Health and Safety Coordinator (RHSC)	. 2-1
	2.4	ESE Corporate Health and Safety Officer (CHSO)	. 2-2
	2.5	ESE Field Implementation Manager (FIM)	. 2-2
	2.6	ESE Field Team Members (FTM)	
3.0	Hazard	lous Substances/Constituents of Concern	. 3-1
4.0	Hazard	l Assessment	. 4-1
5.0	Hazard	d Mitigation and Control	. 5-1
	5.1	General Safety Rules	. 5-1
	5.2	Electrical Hazards	. 5-1
	5.3	Temperature Hazards	. 5-2
		5.3.1 Heat	. 5-2
		5.3.2 Cold	. 5-2
	5.4	Drilling/Boring Hazards	. 5-3
	5.5	Heavy Equipment Hazards	. 5-3
	5.6	Vehicular Hazards	
	5.7	Fire/Explosion Hazards	. 5-5
	5.8	Chemical Hazards	
		5.8.1 Air Monitoring	. 5-5
		5.8.2 Levels of Protection	
		5.8.3 Engineering Control	
	5.9	Noise	
	5.10	Lockout/Tagout	
	5.1 1	Decontamination Procedures	
		5.11.1 Level B	

		5.11.2 Level C	5-8
		5.11.3 Modified Level C	5-9
		5.11.4 Level D	5-9
	5.12	Medical Surveillance Requirements	5-9
	5.13	Training Requirements	5-9
	5.14	Site Control	. 5-10
		5.14.1 Site Work Zones	. 5-10
		5.14.2 Buddy System	
		5.14.3 Site Communications	
6.0	Emerge	ency Information	6-1
7.0	Conting	gency Plan	7-1
	7.1	Emergency Communications	
	7.2	Emergency Response	
	7.3	Fire or Explosion Response	
	7.4	Spill Response	
		7.4.1 Spill Reporting Procedures	
	7.5	Medical Emergency	
	7.6	Emergency Decontamination Procedures	
	7.7	Chemical Exposure Emergency	
	7.8	Severe Weather Procedure	

List of Tables

Table 3-1 Identified/Suspected Site Constituents of Concern

Table 3-2 Site Chemical Inventory

Table 4-1 Task Hazard Evaluation

Table 4-2 Levels of Protection

Table 6-1 Emergency Information

List of Figures

Figure 1-1 Facility/Site Map

Figure 2-1 HASP Organization Chart

Figure 6-1 Route to Medical Facility (Christian Hospital - Northwest)

List of Appendices

Appendix A Daily Safety Meeting Checklist

Appendix B Log of Site-Specific Training

Appendix C Material Safety Data Sheets

Appendix D Personal Exposure Monitoring Forms

Appendix E Personal Protective Equipment Assessment Form

Appendix F Subcontractor Coordination Checklist

Appendix G McDonnell Douglas Vendor/Contractor Safety/Environmental
Awareness Guide

Appendix H Report of Occupational Accident, Injury or Illness

1.0 Introduction

1.1 Site Information

The McDonnell Douglas (MD) facility (Facility) is located in the northwest portion of St. Louis, St. Louis County, Missouri. MD manufactures combat aircraft, transport aircraft, space systems and missiles, and information systems. The primary product produced at the Facility is combat aircraft, including the F-15 Eagle, the F/A-18 Hornet, and the AV-6B Harrier. Other products produced at the Facility include the T45TS trainer, missile systems, and components for the C-17 transport plane.

Access to the Facility is strictly controlled. The Facility is surrounded by a chain-link fence and patrolled by a security force 24 hours a day, 365 days a year. Employees and visitors must pass through security gates at the main entrance to the Facility before entering any building. The security force employs approximately 225 persons, and an on-site fire department employs approximately 30 persons.

MD began operations in 1941. Currently, the Facility operates 24 hours a day, Monday through Friday. Activities performed in support of MD operations include chemical processing, metal cutting, metal forming and grinding, degreasing, painting, aircraft assembly, aircraft fueling, and aircraft flight testing.

MD is a large quantity generator of hazardous waste. MD generates approximately 48 different waste streams that the Facility considers to be hazardous waste. The largest quantities of waste generated consist of emulsified cutting oil, paint solids, solvent and paint waste, wastewater treatment sludge, acid waste, and caustic waste.

The Facility is surrounded by Lambert -St. Louis International Airport on the south, commercial and industrial facilities on the west and north, and residential areas on the east. Surface water from the Facility drains toward Coldwater Creek which flows along the Facility's eastern boundary.

1.2 Objective

The objective of this HASP is to provide a consistent methodology that addresses the various health and safety concerns during the RFI Phase I Field activities at the Facility. The field activities consist of soil sampling with a Geoprobe system.

1.3 Regulatory Requirements

OSHA standards 29 CFR 1910 and 1926 apply to work under this site-specific safety plan. Detailed OSHA requirements for hazardous waste operations are contained in 29 CFR 1910.120, "Hazardous Waste Operations and Emergency Response." Additional guidance for hazardous waste operations may be found in the EPA publication, "Standard Operating Safety Guides" (November 1984) and in the

National Institute of Occupational Safety and Health (NIOSH)/OSHA/U.S. Coast Guard (USCG)/EPA publication, "Occupational Safety and Health Guidance manual for Hazardous Waste Site Activities" (October 1985).

2.0 ESE Health and Safety Personnel

The following section briefly describes the health and safety designations and general responsibilities that will be employed for the MD project. An organizational chart is included. Overall and final project health and safety is the responsibility of the Project Manager, whether handled by them personally or by designated individuals.

2.1 Site Health and Safety Officer (SHSO)

The ESE Site Health and Safety Officer (ESE SHSO) has the responsibility to implement this HASP. The ESE SHSO will conduct safety inspections and investigate each accident, illness, injury, and incident resulting from field activities under this task. The ESE SHSO will also conduct daily safety meetings, complete the daily safety meetings checklists (Appendix A), and conduct site-specific training for on-site personnel (Appendix B). As necessary, the ESE SHSO will accompany any governmental agency personnel from the Missouri Department of Natural Resources (MDNR), Occupational Safety and Health Administration (OSHA), or other agency personnel visiting the Facility in response to health and safety issues. The ESE SHSO, in consultation with the ESE Local Health and Safety Representative (ESE LHSR), is responsible for updating and modifying this HASP as study area or environmental conditions change.

The ESE SHSO is vested with the authority to stop field operations (STOP WORK AUTHORITY) if he or she determines that an imminent health or safety hazard or other potentially dangerous situation exists. The ESE SHSO may also recommend to the ESE LHSR or ESE Regional Health and Safety Coordinator (ESE RHSC) that the Exclusion Zone authorization of individual site personnel be revoked for health and/or safety causes.

2.2 Local Health and Safety Representative (LHSR)

The ESE Local Health and Safety Representative (LHSR) is the health and safety professional serving as the ESE St. Louis office designee for this project. As such, the ESE LHSR is responsible for 1) reviewing and approving of this site-specific HASP, and any significant changes made over time to the HASP; 2) resolving disputes involving health and safety issues; and 3) assuring implementation of this HASP by the ESE SHSO. The ESE LHSR also conducts safety inspection audits. The ESE LHSR will notify the ESE RHSC of any Stop Work Orders issued by the ESE SHSO.

2.3 ESE Regional Health and Safety Coordinator (RHSC)

The ESE Regional Health and Safety Coordinator (RHSC) has final authority to resolve health and safety issues not resolved at or through the ESE LHSR, and has overall responsibility for assuring that the policies and procedures of this HASP comply with Environmental Science & Engineering, Inc.'s (ESE)

corporate health and safety program and 29 CFR 1910.120. The ESE RHSC will be responsible for the pre-evaluation of subcontractor's health and safety programs.

2.4 ESE Corporate Health and Safety Officer (CHSO)

The ESE Corporate Health and Safety Officer (CHSO) shall be used as a resource for information and advice by the ESE RHSC and LHSR, as needed. The ESE CHSO will be made aware of scheduled field operations in which Level B Personal Protective Equipment (PPE) will be utilized.

2.5 ESE Field Implementation Manager (FIM)

The ESE Field Implementation Manager (FIM) will be responsible for assuring that all field personnel have completed ESE's medical surveillance requirements and health and safety training required by 29 CFR 1910.120. The ESE Task Manager will work in conjunction with the ESE SHSO and ESE LHSR in making decisions regarding health and safety of on-site personnel.

2.6 ESE Field Team Members (FTM)

The ESE Field Team Members (FTMs) will include on-site personnel, other than those mentioned above. Each ESE FTM will have Exclusion Zone authorization.

3.0 Hazardous Substances/Constituents of Concern

Chemical hazards of constituents of concern during activities at MD include: tetrachloroethylene (PCE): 1,2-dichloroethene (1,2-DCE); acetone, xylenes, and polynuclear aromatic hydrocarbons (PAHs) including: anthracene, benzo(k)fluoranthene, benzo(g,h,i)anthracene, benzo(a)pyrene, chrysene, dibenzo(a,h)anthracene, fluoranthene, indeno(1,2,3-cd)pyrene, phenanthrene, and pyrene. The potential inorganics of concern are: arsenic, cadmium, and selenium. A detailed summary of constituents of concern is provided in Table 3-1. Site chemical inventory is presented in Table 3-2. Material Safety Data Sheets (MSDS) for constituents of concern are included in Appendix C.

4.0 Hazard Assessment

Specific hazards associated with individual task/activities at MD are presented in Table 4-1. Table 4-2 presents the level of protection anticipated for each task along with the action level for upgrade and upgrade level of protection.

5.0 Hazard Mitigation and Control

5.1 General Safety Rules

Eating, drinking, chewing gum or tobacco, smoking, and applying lip balm or make-up is prohibited in any area designated as contaminated.

Contact with contaminated surfaces should be avoided. Whenever possible, Field Team Members should not walk through puddles, mud, or discolored surfaces; kneel on the ground; or lean, sit, or place themselves or equipment on drums, vehicles, or the ground.

Contact lenses will not be worn in any areas other than the support zone.

Smoking is prohibited within the fenced area of the Facility. Other sources of ignition are prohibited in the vicinity of heavy equipment and flammable or contaminated material, including flammable vapors.

Personnel must wash hands and face prior to eating and drinking. Field personnel must shower as soon as possible after leaving the site.

Horseplay is prohibited in all work areas.

Working while under the influence of intoxicants, narcotics, or controlled substances is prohibited.

Good housekeeping procedures shall be followed to reduce slips, trips, and falls.

Operations shall be restricted to daylight hours unless adequate lighting is provided (see Attachment F of ESE's UCEP Program).

5.2 Electrical Hazards

Have buried electric lines located and marked by the local authority (e.g., DIGSAFE) before initiating all subsurface work.

For voltages 50 kV or less, maintain at least 10 feet of clearance from overhead power lines. For voltages exceeding 50 kV, the clearance shall be increased by 4 inches for every 10 kV over 50 kV. Contact the electric utility concerning blanketing of overhead power lines if these distances cannot be obtained.

Electrical equipment, including pumps, sampling equipment, and power tools will be inspected prior to use to ensure that they are in good repair and have no frayed or loose connections.

All electrical equipment used on-site will be properly grounded or bonded.

Ground Fault Circuit Interrupters (GFCI) will be used with electrical equipment on all outdoor and subsurface tasks.

If electrical equipment must be connected by splicing wires, use properly insulated connectors and wrap with electrical tape.

Do not perform work on electrical hook-ups and/or equipment when they are located in standing water or any wet location. When water is present, either drain/dry the area or move the equipment to a dry location.

Only properly trained personnel should make electrical connections. If necessary, a master electrician should be subcontracted or the Facility electrical maintenance technician should be contacted.

All electrical equipment will be shut off during fueling operations.

5.3 Temperature Hazards

5.3.1 Heat

When work is being performed under high temperatures and humidity, implement a heat stress monitoring program according to SOP 340. Monitoring should include heart rate and body temperature measurements.

Work/rest periods should be modified as necessary based on the results of the monitoring program.

Preventative measures should be taken to avert employee illness, including rest periods, work slowdowns, job rotation, and/or performing work during cooler hours of the day. Shade or airconditioned shelter should be provided for employees during rest periods.

Potable, cool water will be provided for employees. Workers should be encouraged to drink 16 ounces of water prior to their shift, and drink at every rest break (or every 15 to 20 minutes).

The SHSO or FIM will discuss the signs and symptoms of heat related illnesses with workers and document on the Daily Safety Meeting Checklist.

5.3.2 Cold

In cold extremes, if feet or other body parts become wet they should be dried at the earliest possible time. If this occurs on a boat and the individual must be returned to shore, care should be taken during boat travel to avoid aggravating the problem with increased wind chill.

After going through the decontamination procedures, employees should proceed directly to a protected area.

At temperatures of 32°F, the effects of wind speed become pronounced. A tarp or other barrier should be used to reduce the effects of wind speed if possible. A protected area will be provided for employees for rest breaks.

Protective clothing shall be used, especially on the head, neck, and hands, to the extent possible to reduce chances of hypothermia and frostbite.

Avoid skin contact with metal objects. Tools and equipment with nonmetallic handles should be used when possible.

The SHSO or FIM will discuss the signs and symptoms of cold weather injuries with workers and document on the Daily Safety Meeting Checklist.

5.4 Drilling/Boring Hazards

A warning device or signal person shall be provided to protect employees from moving drilling/boring equipment. For signal person: Where hand signals are used, only one person shall be the designated signal person, and shall be located to see the load and be clearly visible to the operator.

Employees are not allowed under, on, or in a derrick being raised or lowered.

Employees shall obtain instructions from the drilling operator as to where to locate themselves to prevent accidents from hoists, augers, etc.

ESE's Lockout/Tagout Program shall be followed during maintenance or repair activities.

All personnel shall be informed by the appropriate equipment operator of the location of the "kill switch" for each piece of equipment on-site.

Loose fitting clothing and long hair that is not adequately tied up are not allowed when working in the vicinity of the drilling/boring equipment.

ESE personnel should not attempt to obtain samples from operating drilling equipment.

5.5 Heavy Equipment Hazards

A warning device or signal person shall be provided to protect employees from moving drilling/boring equipment. For signal person: Where hand signals are used, only one person shall be the designated signal person, and shall be located to see the load and be clearly visible to the operator.

Employees are not permitted underneath loads handled by lifting or digging equipment. Employees shall also stay clear of any vehicle being loaded or unloaded.

Seatbelts shall be worn if available, except for equipment designed for stand-up operation.

Equipment shall be shut down during refueling.

Loose fitting clothing and long hair that is not adequately tied up are not allowed when working in the vicinity of heavy equipment.

5.6 Vehicular Hazards

The local traffic control authority shall be contacted prior to interrupting the flow of public travel.

Employees exposed to public vehicular traffic shall wear warning vests marked with or made of reflective or high-visibility material.

Public traffic shall be protected from site hazards by placing traffic cones, barricades, construction fencing, etc. at a safe distance around the work site.

Seat belts shall be worn when driving or a passenger in a vehicle.

Always remember that when you are trailering a boat, once underway it is easy to lose a feel for the tow. Allow more room to stop and greater clear distance for overtaking and passing other vehicles.

Be alert for signs restricting trailers.

Continually check and/or monitor that the trailer features (i.e., wheel bearings, tie downs, lights) are in good shape and proper working condition during the trip.

A warning or signal shall be provided to protect employees from a moving truck and boat trailer. For signal person: where hand signals are used, only one person shall be the designated person, and shall be located to see the trailer and be clearly visible to the truck operator.

5.7 Fire/Explosion Hazards

Explosive Atmosphere -

10% LEL Proceed with work

10 - 20% LEL

Monitor with extreme caution; no hot work permitted.

20% LEL Evacuate work zone immediately

Keep all sources of ignition away from explosive atmosphere and flammable materials.

Use intrinsically safe instrumentation in any potentially explosive atmosphere.

All flammable liquids shall be kept in approved containers.

5.8 Chemical Hazards

5.8.1 Air Monitoring

5.8.1.1 Equipment Required

Air monitoring equipment to be used on-site includes: PID (11)

5.8.1.2 Frequency

Upon initial site entry, air monitoring shall be performed in accordance with the UCEP Program in order to properly characterize the site and obtain adequate information on hazardous air conditions.

Additional monitoring shall be conducted whenever work begins on a different portion of the site; when different contaminants are handled, encountered, or suspected to be encountered; when a different operation is initiated; in the event of a spill or leak; and whenever the SHSO or FIM determines that additional monitoring is warranted.

5.8.1.3 Air Monitoring Techniques

Air monitoring shall be conducted on the employee(s) who have the potential for the highest exposure to the contaminant(s). Monitoring shall be performed in such a way that personal exposures to the contaminants may be calculated. Airborne levels of contaminants shall be noted periodically in the field log book, and every reading shall be recorded on the appropriate Personal Exposure Monitoring Form (Appendix D). If only representative employees will be monitored, the names of other employees represented by the monitoring shall be noted in the field log book and on the Personal Exposure Monitoring Forms. Integrated, full-shift monitoring requiring laboratory analysis shall not be relied on as the sole means of exposure assessment for any work area or task where conditions may change rapidly.

5.8.1.4 Calibration

All air monitoring instruments shall be calibrated according to manufacturer's instructions and standard industrial hygiene practice (see SOP 140). Direct reading instruments shall be calibrated prior to and after (each day's) use, and at any time the operator of the instrument suspects instrument drift or malfunction. Air sampling pumps shall be calibrated prior to and after each use. Each calibration shall be recorded in the individual instrument log book, as well as on the appropriate Personal Monitoring Forms.

5.8.2 Levels of Protection

5.8.2.1 Level B

Positive pressure, full face-piece self-contained breathing apparatus (SCBA), or positive pressure supplied air respirator with escape SCBA.

- Hooded, full-body chemical-resistant clothing (type: Saranac[®] or equivalent).
- Outer chemical resistant gloves (type: nitrile or equivalent).
- Inner chemical resistant gloves (type:rubber vinyl or equivalent).
- Chemical resistant outer boots and steel toe inner boots; or Chemical resistant, steel toe boots (type--rubber outer boot covers or rubber steel-toed boots).
- Optional items -- hard hat, disposable boot covers, and disposable coveralls for over chemical resistant clothing, hearing protection.

5.8.2.2 Level C

- Full-face air purifying respirator (cartridge type: combination cartridge).
- Chemical resistant clothing (type: Tyvek®, Saranac®, or equivalent).
- Outer chemical resistant gloves (type: nitrile or equivalent).
- Inner chemical resistant gloves (type: rubber vinyl or equivalent).
- Chemical resistant outer boots and steel toe inner boots; or Chemical resistant, steel-toe boots (type -- rubber outer boot covers or rubber steel-toe boots).
- Optional items -- hard hat, disposable boot covers, and disposable coveralls for over chemical resistant clothing, hearing protection.

5.8.2.3 Modified Level C

- Chemical resistant clothing (type: Tyvek®, Saranac®, or equivalent).
- Outer chemical resistant gloves (type: nitrile or equivalent).
- Inner chemical resistant gloves (type: rubber vinyl or equivalent).
- Chemical resistant outer boots and steel-toe inner boots, or Chemical resistant, steel toe boots (type
 rubber outer boot covers or rubber steel-toe boots).

• Optional items -- hard hat, disposable boot covers, and disposable coveralls for over chemical resistant clothing, hearing protection.

5.8.2.4 Level D

- Coveralls or appropriate work clothing.
- Gloves.
- Steel-toe boots.
- Safety glasses with side shields.
- Splash goggles will be the minimum eye protection worn when handling concentrated acids or caustics.
- Optional items -- hard hat, chemical resistant over boots, escape full-face air purifying respirator, face shield, hearing protection.

5.8.2.5 Certification of PPE Hazard Assessment

I certify that the hazard assessment regarding personal protective equipment for ESE's work at MD - St. Louis was completed on May 28, 1997 by Scott George in accordance with 29 CFR 1910.132 and ESE's Personal Protective Equipment Program (Appendix E). The results of the hazard assessment are incorporated in the PPE requirements noted above.

Jouglas J. Warran
Signature of Project Manager

5.8.3 Engineering Control

Measures shall be taken on-site to reduce airborne dust levels when visible airborne dust becomes present. Water or other appropriate dust suppressant materials shall be applied to work and traffic areas as appropriate to reduce the amount of dust generated.

5.9 Noise

Noise monitoring should be conducted on a periodic basis to determine the need for hearing protection. Alternatively, the use of hearing protection can be based on historical data for a similar project. Hearing protection, with the appropriate attenuation factor, will be worn by all employees in the area when noise levels meet or exceed 85 dB(A). The Field Implementation Manager shall strictly enforce the use of appropriate hearing protection when noise levels exceed 90 dB(A).

5.10 Lockout/Tagout

All hazardous sources of energy, including electrical, mechanical, pressure, thermal, stored energy, and hazardous chemicals or other agents, must be locked out in accordance with ESE's Lockout/Tagout

Program. Lockouts may only be performed by Authorized Employees who have successfully completed the training outlined in SOP 535.

Locks and tags shall be used whenever the equipment is capable of handling a lock. Tags alone are only permitted where the equipment was designed without the capability of being locked. Every energy source associated with the equipment must be locked/tagged out. Every individual working on the equipment shall apply his/her own lock. All lockout/tagout equipment must be approved by ESE for use. The lockout/tagout procedures outlined in SOP 530 shall be followed.

5.11 Decontamination Procedures

5.11.1 Level B

Station 1:Outer glove wash (tap water with Alconox®)

Station 2:Outer boot and glove rinse (tap water)

Station 3:Tape Removal

Station 4:Outer boot and glove removal

Station 5:Suit and inner boot wash (tap water with Alconox®)

Station 6:Suit and inner boot rinse (tap water)

Station 7:Inner boot removal

Station 8:Suit and hard hat removal

Station 9:SCBA Backpack Removal

Station 10:Inner glove wash (tap water with Alconox®)

Station 11:Inner glove rinse (tap water)

Station 12:Face-piece removal

Station 13:Inner glove removal

Station 14:Inner clothing removal

Station 15:Field hand/face wash or shower

All disposable items will be bagged for appropriate disposal.

5.11.2 Level C

Station 1:Outer boot and glove wash (tap water with Alconox®)

Station 2:Outer boot and glove rinse (tap water)

Station 3:Outer boot and glove removal

Station 4:Coverall removal

Station 5:Respirator removal and wipe down

Station 6:Inner glove removal and hand wash/rinse

All disposable items will be bagged for appropriate disposal.

5.11.3 Modified Level C

Station 1:Outer boot and glove wash (tap water with Alconox®)

Station 2:Outer boot and glove rinse (tap water)

Station 3:Outer boot and glove removal

Station 4:Coverall removal

Station 5:Inner glove removal and hand wash/rinse

All disposable items will be bagged for appropriate disposal.

5.11.4 Level D

Station 1:Boot and glove wash

Station 2:Boot and glove rinse (tap water)

Station 3:Boot and glove removal

Station 4:Hand wash/rinse

All disposable items will be bagged for appropriate disposal.

5.12 Medical Surveillance Requirements

All site personnel shall be actively participating in ESE's Medical Surveillance Program, including baseline and annual examinations at an EMR clinic and in accordance with 29 CFR 1910.120 and 29 CFR 1910.134. A copy of each employee's Medical Summary form will be retained on-site. At least one field team member will be trained and certified in CPR and First Aid.

For any exposure incidents while rendering first aid or CPR, the exposed individuals shall receive a medical evaluation and Hepatitis B vaccination in accordance with ESE's Bloodborne Pathogen Program. The LHSR and EMR shall be notified immediately of any exposure incidents.

ESE's OSHA 200 Log is kept on file at ESE's St. Louis office.

5.13 Training Requirements

All workers will complete 40-hour training in accordance with SOP 200 prior to working on-site. This training shall be kept current via 8-hour refresher training in accordance with SOP 201.

SHSOs and FIMs shall also have successfully completed 8 hours of supervisor training in accordance with SOP 202.

At least one field team member shall be trained and certified in first aid and CPR. Personnel who have received this training must also receive the appropriate level of bloodborne pathogen training in accordance with SOP 610.

All workers shall have successfully completed respirator training in accordance with SOP 400 for the appropriate type(s) of respirator.

All workers shall have successfully completed personal protective equipment training in accordance with SOP 425 and ESE's Personal Protective Equipment Program.

Prior to commencement of site activities and daily thereafter, site specific training will be provided in accordance with SOP 203 and will include an overview of HASP requirements. The Daily Safety Meeting Checklist included as part of this HASP will be used to document this training. Subcontractors will be required to read the HASP prior to commencement of field activities. The Project Manager will complete a subcontractor coordination checklist. A copy of the subcontractor coordination checklist is included in Appendix F.

Employees involved in any lockout and/or tagout procedure on-site shall have successfully completed training for Authorized Employees in accordance with SOP 535 Section 5.2. Employees working nearby or otherwise affected by the lockout/tagout activities shall receive training for Affected Employees in accordance with SOP 535 Section 5.1.

All ESE or subcontracted personnel must review MD's Vendor/Contractor Safety/Environmental Awareness Guide prior to entering the site. MD's Awareness guide must be followed when no corresponding ESE procedure is available for the tasks or situation.

5.14 Site Control

5.14.1 Site Work Zones

Three work zones shall be established on-site as deemed appropriate and feasible by the FIM: Exclusion Zone, Contamination Reduction Zone, and Support Zone. Site work zone delineation will be based on the site activities and on the size and configuration of the site. Support zones shall be established upwind of the Exclusion Zone and field activities. Wind direction may be determined by visual observation or field instrumentation. Work zones shall be delineated using barrier tape or other effective means.

The Exclusion Zone will be the immediate area around field activities where contamination does or could occur. The Contamination Reduction Zone is the transition between the contaminated area and the clean area. The Contamination Reduction Zone should be designed to limit, as much as possible, the probability of the Support Zone becoming contaminated. The Support Zone is considered to be a "clean" area; all administrative and other support services should be performed in the Support Zone.

5.14.2 Buddy System

Site personnel must practice the buddy system of at least two people who maintain visual or verbal contact within an exclusion zone. Contact should be either constant or at some frequent interval during field work (frequency should depend on the nature of hazards present). The buddy may be an ESE employee, subcontractor, or client representative as appropriate. For normal Level D activities, the buddy system will consist of the individual performing the work notifying on-site personnel of his/her presence at the Facility. On-site personnel include MD personnel, on-site subcontractors, or Facility guards.

5.14.3 Site Communications

Telephones are present at the guard buildings located at the plant entrances, at waste treatment, and various other buildings and construction support structures (construction trailers). Two-way radios are available from Environmental Engineering when needed.

6.0 Emergency Information

This section provides information that would be used under emergency conditions. Table 6-1 identifies site resources and locations. Figure 6-1 shows the route to the medical facility. Appropriate local resources such as nearest medical facility, police, and fire department are listed along with their respective addresses and phone numbers. ESE emergency resources are also listed.

7.0 Contingency Plan

7.1 Emergency Communications

The MD emergency notification system for all emergencies consists of calling 911 and giving the following information.

- 1. Your name and employers name
- 2. Phone number from which you are calling
- 3. Location of the incident
- 4. Nature of the emergency

7.2 Emergency Response

MD's emergency evacuation procedures and emergency evacuation route are in the Vendor/Contractor Safety/Environmental Awareness Guide included in Appendix G.

7.3 Fire or Explosion Response

In the event of a fire or explosion, the area will be immediately evacuated and 911 dialed as soon as possible. The Fire Department will also be summoned. If at all possible, workers in the exclusion zone will exit through the contamination reduction zone and will, at a minimum, remove or scrub their outer boots and remove their outer layer of protective clothing prior to proceeding to the assembly location. Site personnel will gather at a designated location upwind of the fire/explosion (use predominant wind direction). The location shall be established during the daily safety meeting, and a head count will be taken at the location. Upon their arrival, notify the fire department of the location and nature of the fire/explosion. Also provide information on the location and identification of hazardous and flammable materials on-site.

If it can be done safely, site personnel who have had the appropriate training may perform the following:

- Use available on-site fire extinguisher to control or extinguish the fire if it is small and localized;
- Remove or isolate flammable or other hazardous materials that may contribute to the fire;
- Begin containment and recovery of any spilled materials (see below).

7.4 Spill Response

In the event of a spill, the SHSO and the MD Project Manager shall be notified immediately. Procedures for exposure monitoring and control as outlined in this HASP shall be followed, including upgrading the LOP for spill containment/clean-up if necessary. FTMs should stop the spill source and contain and cleanup the spill as necessary and appropriate. After the cleanup is completed, air monitoring will be conducted by the SHSO to ensure that airborne levels of the contaminant(s) are at a safe or appropriate level.

7.4.1 Spill Reporting Procedures

Any spill of a hazardous substance over 10 gallons must be immediately reported to MD's Project Manager. The MD Project Manager will conduct the necessary reporting requirements. Further discussion of spill reporting procedures is presented in the MD Vendor/Contractor Safety/Environmental Awareness Guide included in Appendix G.

7.5 Medical Emergency

If trained and willing, initiate first aid and get medical attention for the injured person(s) immediately. Have the injured person(s) transported to the nearest medical facility (see above) or dial 911 as necessary. As soon as possible, notify the injured person's supervisor, the MD Project Manager, and/or the ESE Project Manager. Supervisors/PM's notify your LHSR and, in the event of a chemical or bloodborne pathogens exposure, EMR immediately. As soon as possible after the incident, an ESE Report of Occupational Accident, Injury or Illness (Appendix H) must be submitted to the appropriate individual.

7.6 Emergency Decontamination Procedures

The level of decontamination in a medical emergency will be determined by the extent of the injury. For minor injuries, personnel must go through the proper decontamination sequence as stated in this HASP.

In life-threatening emergencies or when decontamination may aggravate the condition, decontamination procedures may be omitted. If decontamination cannot be performed, a FTM should accompany the injured worker to the medical facility, if possible, to provide information to medical response personnel regarding the contaminants and decontamination procedures. In lieu of decontamination, actions such as removal of the outer layer of protective clothing or wrapping the victim in plastic (during treatment) can be taken if they will not delay or interfere with the treatment of the injury. In the event the victim has been splashed with a corrosive material, the affected area should always be flushed with water (see below).

7.7 Chemical Exposure Emergency

EYE CONTACT:

Flush eyes with copious amounts of water for 15 minutes.

SKIN CONTACT:

Remove contaminated clothing. Flush skin with copious amounts of water for

15 minutes.

INHALATION:

Remove to fresh air.

INGESTION:

Consult Poison Control Center, MSDS or other appropriate medical resource

(see above).

7.8 Severe Weather Procedure

Upon hearing a "TAKE COVER" announcement, or seeing a tornado, severe thunderstorm, or other severe weather, all personnel will immediately take cover. Personnel will report to the Environmental & Hazardous Materials Services (EHMS) after an "ALL CLEAR" notice is received to report any incidences that may have occurred.

Table 3-1. Identified/Suspected Site Constituents of Concern, McDonnell Douglas, St. Louis, Missouri

Constituent Name (Synonyms)	Appearance & Physical Form (Pure substance)	OSHA PEL/ ACGIH TLV	STEL	IDLH	Routes of Entry	Potential Health Effects (Acute & Chronic)	PID Ionization Potential
Acetone	Colorless liquid with fragrant mint- like odor	750 ppm (PEL)	1000 ppm	2500 ppm	Inhalation Ingestion Contact	Irrit eyes, nose, throat; head, dizz, CNS depress; derm	9.69
Arsenic (inorganic)	METAL-silver-grey or tin-white, brittle, odorless solid	0.01 mg/m³ (TLV)	NE	5 mg/m³	Inhalation Ingestion Contact	Ulceration of nasal septum, derm, GI disturbances, peri neur, resp irrit, hyperpig of skin (carc)	9.89
Benzo(k)Fluoranthene		NE	NE	ND	Inhalation Ingestion Contact	Experimental tumorigen, irritating fumes when heated	
Cadmium	METAL silver-white, blue-tinged, lustrous, odorless solid	0.005 mg/m³	NE	9 mg/m³	Inhalation Ingestion	Pulm edema, dysp, cough, chest tight, subs pain; head; chills, musc aches; naus, vomit, diarr, anos, emphy, prot, mild anemia [carc]	NA
1,2-Dichloroethene (1,2-Dichloroethylene)	Colorless liquid with a slightly acrid chloroform-like odor	200 ррт	NE	1000 ppm	Inhalation Ingestion Contact	Irrit eyes, resp sys, CNS depres	9.65
Selenium	Amorphous or crystalline, red to grey solid	0.2 mg/m³	NE	1 mg/m³	Inhalation Ingestion Contact	Irrit eyes, skin, nose, throat, vis dist; head; chills, fever, dysp, bron; metallic taste, garlic breath, GI dist; derm; eye, skin burns	NA

Constituent Name (Synonyms)	Appearance & Physical Form (Pure substance)	OSHA PEL/ ACGIH TLV	STEL	IDLH	Routes of Entry	Potential Health Effects (Acute & Chronic)	PID Ionization Potential
Tetrachloroethylene (perchlorethylene, perk)	Colorless liquid with a mild chloroform-like odor	25 ppm	100 ppm	150 ppm	Inhalation Absorption Ingestion Contact	Irrit eyes, nose, throat, nau; flush face, neck; vert, dizz, inco; head, som; skin eryt; liver damage; [carc]	9.32
Xylenes (o-,m-,p-isomers)	Colorless liquid with an aromatic odor	100 ррт	150 ppm	900 ppm	Inhalation Absorption Ingestion Contact	Irrit eyes, skin, nose, throat; dizz, excitement, drow, inco, staggering gait, corn vacuolization, anor, nau, vomit, abdom pain, derm	8.44-8.56

Note:

STEL = Short Term Exposure Limit (STEL)

IDLH = Immediately Dangerous to Life and Health

OSHA = Occupational Safety and Health Administration

PEL = Permissible Exposure Limit

TLV = Threshold Limit Value

ppm = parts per million

ACGIH = American Conference of Governmental Industrial Hygienists

NIOSH = National Institute of Occupational Safety and Health

ND = Not Determined

NA = Not Applicable

NE - Not Established

mg/m³ = milligrams per cubic meter

Ca/carc = Carcinogen

Abbreviations in table taken from the NIOSH Pocket Guide to Chemical Hazards

Table 3-2. Site Chemical Inventory, McDonnell Douglas, St. Louis, Missouri

Chemical Name (Match to MSDS)	Estimated Quantity On-site at Any Given Time	Location On-site
Acetone	1 liter	in vehicle

A current MSDS must be present on site for each chemical listed above. All chemical containers must be labeled in accordance with SOP 150. Subcontractors must maintain their own chemical inventory.

U.S. GEOLOGICAL SURVEY, 7.5 MINUTE SURVEY (TOPOGRAPHIC) FLORISSANT, MO. QUADRANGLE (1954), PHOTOREVISED 1982. SOURCE: Hazalwood SITE AMBÉRT ST LOUIS PNATIONAL AIRPORT 1000 2000 MISSOURI APPROXIMATE SCALE IN FEET McDONNELL DOUGLAS

Figure 1-1
FACILITY SITE MAP

Appendix A

Daily Safety Meeting Checklist

Daily Safety Meeting Checklist

Projec	t: McDonnell Douglas	Site: St. Louis, Missouri 6	3166-0516
Projec	t Number: 5197042-	Date:	
Altern Locati Site T	To be reviewed on the first day of site activities and Safety Officer: ate for Health and Safety: on of On-site HASP: raining Requirements: ic Medical Surveillance Requirements:		
	the project, one or more of the agenda items could be selected for the daily site training. Agenda	Date:	Check-off
1. 2. 3. 4. 5.	Safety glasses/goggles Hard hat _ANSI approved Foot protection _Safety Boots		
7. 8. 9. 10. 11. 12.	Inner gloves Outer gloves Hearing protection Other Review inspection, decontamination, and maintenance proof the above stated PPE. Decontamination procedure (discuss/review) Exclusion zone established. Radius 15 ft (specify) Site emergency response plan (discuss/review) Signs and symptoms of overexposure to chemicals anticipal General health and safety rules Specific health and safety requirements relating to site activities	cedures and the limitations	
14.	(discuss/review) Drilling/boring UST Excavations Heavy equipment Confined space entry Lockout/tagout Working in temperature extremes Other health and safety issues (discuss/note)		

Daily Safety Meeting Checklist (cont.)

articipated in the daily safety meeting discussing the to bility for complying with all health and safety requires nealth and safety issues and procedures answered. Employee (Name and Signature)	Employee Number	Date
antition of the state of the st		
	V	

Appendix B

Log of Site-Specific Training

LOG OF SITE-SPECIFIC TRAINING

roject	`	Project No.	
onics Covere	ed:		
	ed:		
	- 100		
8	<u>a</u>		
£ =			
Employe	e's Signature	Employee Number	Date
Employe	e's Signature	Employee Number	Date
Employe		Employee Number	Date
Employe		Employee Number	Date
· · · · · · · · · · · · · · · · · · ·		Employee Number	Date
		Employee Number	Date
· · · · · · · · · · · · · · · · · · ·		Employee Number	Date
•		Employee Number	Date

Appendix C

Material Safety Data Sheets

MALLINCKRODT

Material Safety Data Sheet

Mallinckrodt, Inc. Science Products Division, P.O. Box M Paris, KY 40361

Individuals receiving the information must exercise their independent judgment in determining its appropriateness for a particular purpose. MALLINCKRODT MAKES NO REPRESENTATIONS, OR

WARRANTIES, EITHER EXPRESS OR IMPLIED, OF

Mallinckrodt provides the information contained herein in good faith

but makes no representation as to its comprehensiveness or accuracy.

MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE WITH RESPECT TO THE INFORMATION SET FORTH HEREIN OR TO THE PRODUCT TO WHICH THE INFORMATION REFERS. ACCORDINGLY, MALLINCKRODT WILL NOT BE RESPONSIBLE FOR DAMAGES RESULTING FROM USE OF OR RELIANCE UPON THIS INFORMATION.

Emergency Telephone Number: 314-982-5000

ACETONE

PRODUCT IDENTIFICATION:

Synonyms: Dimethylketone; 2-propanone

Formula CAS No.: 67-64-1

Molecular Weight: 58.08

Chemical Formula: CH3COCH3

Hazardous Ingredients: Acetone

PRECAUTIONARY MEASURES

DANGERI EXTREMELY FLAMMABLE. HARMFUL IF SWALLOWED OR INHALED. CAUSES IRRITATION.

Keep away from heat, sparks and flame. Avoid contact with eyes, skin and clothing. Keep container closed. Use with adequate ventilation. Avoid breathing vapor.

EMERGENCY/FIRST AID

if swallowed, induce vomiting immediately by giving two glasses of water and sticking finger down throat. Never give anything by mouth to an unconscious person. If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. In case of contact, Immediately flush skin or eyes with plenty of water for at least 15 minutes. In all cases call a physician. SEE SECTION 5.

DOT Hazard Class: Flammable Liquid

SECTION 1 Physical Data

Appearance: Clear, colorless, volatile liquid.

Odor: Fragrant, mint-like

Solubility: Miscible in all proportions in water.

Boiling Point: 56.5°C (133.7°F) Meiting Point: -95°C (-139°F)

Specific Gravity: 0.8

Vapor Density (Air=1): 2.0

Vapor Pressure (mm Hg): 400 @ 39.5°C (103°F) Evaporation Rate: (Butyl Acetate = 1) ca. 7.7

SECTION 2 Fire and Explosion Information

Fire:

Flammable liquid! Flash point:-18°C (0°F) closed cup Autoignition temperature: 465°C (869°F) Flammable limits in air, % by volume:

lel: 2.6 uel:12.8

Explosion:

Above flash point, vapor-air mixtures are explosive within flammable limits noted above.

Fire Extinguishing Media:

Water, dry chemical, foam or carbon dioxide. Water spray may be used to keep fire exposed containers cool.

Special Information:

In the event of a fire, wear full protective clothing and NIOSH-approved self-contained breathing apparatus with full facepiece operated in the pressure demand or other positive pressure mode. Water may be used to flush spills away from exposures and to dilute spills to non-flammable mixtures.

SECTION 3 Reactivity Data

Stability:

Stable under ordinary conditions of use and storage.

Hazardous Decomposition Products:

Carbon dioxide and carbon monoxide may form when heated to decomposition.

Hazardous Polymerization:

Will not occur.

Incompatibilities:

Oxidizing materials, chloroform, alkalies, acids, potassium t-butoxide.

SECTION 4 Leak/Split Disposal Information

Isolate or enclose the area of the leak or spill. Remove all sources of ignition. Clean-up personnel require protective clothing and respiratory protection from vapors. Contain and recover liquid for reclamation when possible. Larger spills and lot sizes can be collected as hazardous waste and atomized in a suitable RCRA approved combustion chamber, or absorbed with vermiculite, dry sand, earth or similar material for disposal as hazardous waste in a RCRA approved facility. Do not flush to sewer!

Reportable Quantity (RQ)(CWA/CERCLA): 5000 lbs.

Ensure compliance with local, state and federal regulations.

SECTION 5 Health Hazard Information

A. EXPOSURE / HEALTH EFFECTS

Inhalation:

Irritating to the nose, throat, and mucous membranes. May cause dizziness, duliness, and headache. Narcotic in high concentrations.

Ingestion:

May produce narcotic effects with other symptoms paralleling those from inhalation exposure.

Skin Contact:

Irritating due to defatting action on skin. May cause redness, pain, drying and cracking of the skin.

Eye Contact:

Vapors are Irritating to the eyes. Splashes may cause severe Irritation, with redness and pain.

Chronic Exposure:

Prolonged or repeated skin contact may produce severe irritation or dermatitis.

Aggrevation of Pre-existing Conditions: Use of alcoholic beverages enhances toxic effects.

B. FIRST AID

Inhalation:

Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Call a physician.

Ingestion:

If swallowed, induce vomiting immediately by giving two glasses of water and sticking finger down throat. Never give anything by mouth to an unconscious person. Call physician immediately.

Skin Exposurer

Remove any contaminated ciothing. Wash skin with soap or mild detergent and water for at least 15 minutes. Get medical attention if irritation develops or persists.

Eye Exposure:

Wash eyes with plenty of water for at least 15 minutes, lifting lower and upper eyelids occasionally. Get medical attention immediately.

C. TOXICITY DATA (RTECS, 1986)

Oral rat LD50: 9750 mg/kg Skin rabbit LD50: 20 gm/kg Mutation references cited. Irritation eye rabbit 3.95 mg Severe Aquatic toxicity rating: TLm96: over 1000 ppm

SECTION 6 Occupational Control Measures

Airborne Exposure Limits:

-OSHA Permissible Exposure Limit (PEL); 750 ppm (TWA), 1000 ppm (STEL)

-ACGIII Threshold Limit Value (ILV): 750 ppm (IWA), 1000 ppm (STEL)

Ventilation System:

A system of local and/or general exhaust is recommended to keep employee exposures below the Airborne Exposure Limits. Local exhaust ventilation is generally preferred because it can control the emissions of the contaminant at its source, preventing dispersion of it into the general work area. Please refer to the ACOHI document, "Industrial Ventilation, A Manual of Recommend-Practices", most recent edition, for details.

Personal Respirators: (NIOSH Approved) · If the TLV is exceeded a full facepiece chemical cartridge respirator may be worn, in general, up to the maximum use concentration specified by the respirator supplier. Atternatively, a supplied air full facepiece respirator or airlined hood may be worn.

Skin Protection:

Wear impervious protective clothing, including boots, gloves, lab coal, apron or coveralis to prevent akin contact.

Eye Protection:

Use chemical safety goggles and/or a full face shield where spinshing is possible. Contact lenses should not be worn when working with this material. Maintain eye wash fountain and quick-drench facilities in work area.

SECTION 7 Storage and Special Information

Protect against physical damage. Store in a cool, dry well-ventilated location, away from any area where the fire hazard may be scute. Outside or detached storage is preferred. Separate from oxidizing materials. Containers should be bonded and grounded for transfers to avoid static sparks. Storage and use areas should be No Smoking areas. Use non-sparking type tools and equipment.

ACCET

MALLINCKRODT

Material Safety Data Sheet

Mallinckrodt, Inc. Science Products Division, P.O. Box M Paris, KY 40361

Mallinckrodt provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. Individuals receiving the information must exercise their independent judgment in determining its appropriateness for a particular purpose. MALLINCKRODT MAKES NO REPRESENTATIONS, OR WARRANTIES, EITHER EXPRESS OR IMPLIED, OP

MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE WITH RESPECT TO THE INFORMATION SET FORTH HEREIN OR TO THE PRODUCT TO WHICH THE INFORMATION REFERS. ACCORDINGLY, MALLINCKRODT WILL NOT BE RESPONSIBLE FOR DAMAGES RESULTING FROM USE OF OR RELIANCE UPON THIS INFORMATION.

Emergency Telephone Number: 314-982-5000

Addendum to Material Safety Data Sheet

REGULATORY STATUS

This Addendum Must Not Be

Detached from the MSDS

Identifies SARA 313 substance(s)

Any copying or redistribution of the MSDS

must include a copy of this addendum

(Chem.Key: ACCET)

Product or Components of Product:

ACETONE (67-64-1)

Hazard Categories for SARA
Section 311/312 Reporting
Acute Chronic Fire Pressure Reactive
X X

RCRA CERCLA Sec.103 SARA Section 313 Chemicals SARA EHS Sect. 302 Sec. 261.33 RQ (lbs.) **Chemical Category** Name List TPQ (lbs.) RQ (lbs.) U002 5000 No Yes No No

SARA Section 302 EHS RQ: Reportable Quantity of Extremely Hazardous Substance, listed at 40 CFR 355.

SARA Section 302 EHS TPQ: Threshold Planning Quantity of Extremely Hazardous Substance. An asterisk (*) following a Threshold Planning Quantity = 10,000 LBS. signifies that if the material is a solid and has a particle size equal to or larger than 100 micrometers, the Threshold Planning Quantity = 10,000 LBS. SARA Section 313 Chemicals: Toxic Substances subject to annual release reporting requirements listed at 40 CFR 372.65.

SARA Section 313 Chemicals: Comprehensive Environmental Response, Compensation and Liability Act (Superfund). Releases to air, land or water of these hazardous substances which exceed the Reportable Quantity (RQ) must be reported to the National Response Center, (800-424-8802); Listed at 40 CFR 302.4 RCRA: Resource Conservation and Reclamation Act. Commercial chemical product wastes designated as acute hazards and toxic under 40 CFR 261.33

Appendix D

Personal Exposure Monitoring Forms

PROJECT EXPOSURE RECORD

Project:	Project No.:			
Site Health & Safety Officer:				
Date: Temp.:	Weather:	W	/ind:	
Meter: Serial No.:				
Calibrated: Before: YesNo				
Chemical Compounds: Employees On-site:				
Activity (i.e. soil boring, tank decon, etc.)	Time (Military)	Breathing Zone Reading (1)	Background Reading	
Note: (1) Refer to HASP for upgrade s	pecifications			
Signature	.P. corrections	Date:		

Appendix E

Personal Protective Equipment Assessment

ATTACHMENT B PPE ASSESSMENT

·			Date:		
Type of operation or process (describe):				·	
Employee(s) working in the area:					
Engineering/administrative controls currently in use: _				15	
Eye/Face Protection: Potential for flying objects? Potential for chemical splash hazard? Potential for dust? Potential for glare problems?	Laser?		torch work? of pressure from lines?	Yes	No
Sound level measured during peak operation: 8 hour TWA: dB(A)	dB(A	<u>,</u>			
Foot Protection: Potential for handling or carrying heavy objects? Potential for heavy objects to roll over foot? Potential to step on sharp objects?	Yes	No	Comments	₫•	
Hand Protection: Potential for contact with liquid chemicals? Potential for contact with dry chemicals? Potential for work with vibrating equipment? Welding, cutting or torch work? Potential for cuts, abrasions, blisters, etc.?	Yes	No	Comments		
Skin & Body Protection: Potential for contact with liquid chemicals? Potential for contact with dry chemicals? Potential for exposure to non-ionizing radiation?	Yes	No	Comments		
Respiratory Protection: Are airborne levels of contaminants known? If known, do they exceed the PEL/STEL? When was monitoring performed?	Yes	No	Comments		
Head Protection: Will construction activities be involved? Is there a potential for falling objects? Will employees be working below other workers?	Yes	No	Comments		



PPE REQUIRED

Eve/Face Protection:
If required, specify type

Required

Not Required

Hearing Protection:
If required, specify type

Required

Not Required

Foot Protection:
If required, specify type

Required

Not Required

<u>Hand Protection:</u>
If required, specify type

Required

Not Required

Skin & Body Protection: If required, specify type

Required

Not Required

Respiratory Protection:
If required, specify type

Required

Not Required

<u>Head Protection:</u>
If required, specify type

Required

Not Required



Appendix F

Subcontractor Coordination Checklist

Subcontractor Coordination Checklist

Project:	McDonnell Douglas	Site:	St. Louis, Missouri
			. Kom
Project Number:	5197042	Site Location:	St. Louis, Missouri 63166-0516
I acknowledge that:			
 I have provious this HASP, a field activities 	ded subcontractors who will be per and I have informed the subcontraces.	forming field activities tors that OSHA 29 CFI	on this site with a copy of R 1910.120 applies to their
 I have verific office/division performing of 	ed that all subcontractors working on under ESE's Contractor Pre-Evan-site.	on this project have bee aluation Program for the	en approved for use by the e types of tasks they will be
 I have verifice procedure. 	ed that all subcontractors have a m	ethod to comply with th	ne client's drug surveillance
		Applic	able Not Applicable
	ned all subcontractors that copies of Sheets must be on-site at all times.		nd any applicable Material
program (fro	tagout operations: I have obtained om the subcontractor or LHSR) and eld health and safety training.	information on the sub d have provided that inf	contractor's lockout/tagout formation to the FIM/SHSO
		Appli	cable Not applicable
 I have verifi Specialist). 	ed that all subcontractors have Wo	rkers' Compensation In	surance (see your Contracts
Pro	oject Manager's Signature		Date

Appendix G

McDonnell Douglas Vendor/Contractor Safety/Environmental Awareness Guide

Vendor/Contractor Safety/Environmental Awareness Guide

McDonnell Douglas Aerospace (MDA) St. Louis/St. Charles

McDonnell Douglas Aerospace P.O. Box 516, Saint Louis, MO 63168-0516 (314) 232-0232 TELEX 44-857

Telephone Numbers

For All Emergencies Dial 9-1-1

Additional Numbers for Routine Business

Occupational Safety & Environmental Health (OSEH) 22123

Environmental & Hazardous Materials Services

(EHMS)

23319

Medical Services

22453

Guard Services

22821

Fire Services

22285

Note: The MDA Project Manager is a focal contact point, and as such must be kept fully informed of safety/environmental issues along with other project concerns.

Date Printed: January 1996



Preface

McDonnell Douglas Aerospace recognizes the importance of conducting its business in a socially responsible manner designed to: provide safe and healthful operations for its employees, its customers, and the public; ensure compliance with environmental requirements; and preserve company assets.

It is the responsibility of each Vendor/Contractor to ensure that each Vendor/Contractor employee conducts himself/herself safely, adheres to environmental requirements, and informs MDA when potentially unsafe conditions or environmental risks are observed.

The Vendor/Contractor must assure that this guide is issued to and reviewed by its employees. The receipt found in the back of this guide must be presented to the Security representative at the time of badging.

This booklet serves only as a guide. Nothing herein shall be construed to relieve the Vendor/Contractor of its responsibility to comply with federal, state, and local environmental, health and safety laws, rules, regulations, and MDA Contract requirements. Vendor/Contractor employees violating any of these rules or requirements are subject to removal from the site immediately.

Table of Contents

]	Page
I.	Emergency Procedures	4
II.	General Information	5
III.	Safety/Industrial Hygiene	11
IV.	Environmental Protection	18
V.	Fire Prevention	21
VI.	Security/Site Access	22
VII.	Visitor Guide Maps	24
viii	Guide Receipt	33

2

Section I

Emergency Procedures

1. For All Emergencies dial 9-1-1

- a. Give the following information:
 - Your name and your employer's name
 - Phone number from which you are calling
 - Location of incident
 - Nature of emergency ...
- b. DON'T HANG UP until told to do so! You are a vital line in the emergency and must relay changes in the state of the emergency.

2. First Aid/Medical

 a. MDA will not provide or be responsible for any medical treatment or hospital services.

3. Accident Reporting

a. All accidents resulting in injury to any Vendor/Contractor employee on MDA premises must be promptly reported to the MDA Project Manager or other management, as appropriate.

4. Alarms

a. Two distinctive alarms are used at MDA-St. Louis/St. Charles to warn of a tornado or building evacuation. Project Manager will provide a location for personnel to assemble which will not interfere with emergency vehicles. b. In the event of imminent tornado activity, a warbling tone will sound, indicating that all personnel should seek shelter.

c. A whooping alarm is used in the event of **fire** to warn personnel to evacuate the building.

5. Chemical Spills

a. All spills must be immediately reported by dialing 9-1-1. Spills of chemicals, fuels, oils and other polluting substances must be contained and kept away from all drains, if you can do so safely.

Section II

General Information

1. Site Rules

- a. Vendor/Contractor personnel shall not run in plant or on company premises, including parking lots or roadways. Horseplay of any type will not be tolerated.
- b. Vendor/Contractor employees shall not engage in conduct described below.
 - Smoking in the following prohibited areas: Offices, cafeterias, hallways, and stairwells, factory aisles and tunnels, elevators, flight ramps, and other areas where a lighted smoking device would

- interfere with the protection of lives, equipment, and/or for other safety reasons.
- Possession of weapons, explosives, cameras, radios, cassette player/recorder, electronic and other transmitting or receiving devices.
- Violation of MDA Affirmative Action and Equal Opportunity Policies, which prohibit discrimination, retaliation or harassment (including slurs, banter, writings, pictures, etc.).
- Violation of rules, procedures or warning signs pertaining to employee safety, fire prevention and environmental protection.
- Failure to immediately report personal injuries sustained at the job site to MDA Project Manager.
- Violation of MDA parking plan and traffic rules, including the violation of public laws while engaged in the work.
- 7. Unsatisfactory conduct (conduct detrimental to the interests of MDA or others).
- 8. Concealing or failing to report an error in the work.

- 9. Distracting attention of others from work.
- 10. Distributing literature (illustrated, written, printed or audio/video taped material of any description) in working areas during work time or engaging in commercial solicitations on MDA premises.
- 11. Carelessness resulting in poor workmanship, delay to work in process, damage or destruction to Company property or the property of others.
- Unauthorized entry or presence on MDA premises or entry in restricted areas without permission.
- 13. Possessing, dispensing, selling, drinking, using or being under the influence of alcoholic beverages, narcotics, drugs (except when taken as directed by a competent medical professional), or similar harmful substances on MDA's premises at any time.
- 14. Permitting others to wear one's identification badge, wearing another person's badge, repeatedly forgetting identification badge, or failure to prominently display identification badge at all times.

- c. Vehicles may not be left unattended in main aisles by Contractor personnel.
- d. Prolonged or unnecessary running of vehicles/ equipment inside the building is prohibited.
- e. Contractor's mobile equipment shall not exceed five miles per hour in the buildings or fifteen miles per hour outside of the buildings.
- f. Contractor's vehicles must stop before proceeding through blind intersections. Pedestrians have the right-of-way. Contractor personnel shall observe all vehicle traffic rules and signs.
- g. Contractor personnel operating vehiclemounted lift platforms (e.g. Marklifts, Condors, etc.) must be trained and qualified in their operation by the contractor. Contractor employees riding in self-propelled articulating boom work platforms shall wear the required safety belts and lanyard. Standing on railing of lift platforms is prohibited.
- 2. Foreign Object Damage (F.O.D.)
 - a. Foreign Objects (F.O.) are defined as "an item alien to aircraft, assembly or other product that has been allowed to remain in the product or is in a position to possibly enter the product." All Contractors should be aware that Foreign Object Damage (F.O.D.)

- and Prevention is the responsibility of everyone on MDA premises, including all Contractor personnel. The primary area of concern for F.O.D. Control and Prevention is inside all manufacturing buildings and the Flight Ramp west of Bldg. 02, around Bldgs. 42, 45, 48 including the Hush Houses and Ramp Shelters. Each Contractor should be aware of F.O.D. prevention whenever they are performing work in or around any production areas in all buildings.
- b. Contractor shall ensure that all vehicles entering a building or the Flight Ramp are free of loose debris which could fall off of the vehicle. MDA Security Officer will inspect each vehicle, including the tires, before it is allowed to enter the Flight Ramp. The Security Officer will require Contractor personnel to remove loose debris or rocks from tire treads before allowing the vehicle to proceed onto the Flight Ramp.
- c. Contractors using self-propelled or handpowered vehicles in buildings and on the Flight Ramp shall ensure that vehicles are cleaned to remove all loose F.O. material prior to delivery to the job site.
- d. The Contractor shall issue special delivery instructions to a concrete company when ordering concrete for a Ramp job site. All

trucks shall be thoroughly washed down to remove F.O. and all rocks shall be removed from the tires. The Security Officer will refuse entry to any truck which fails to comply with this requirement.

3. Ramp Area Traffic Rules

Contractor personnel shall observe the following:

a. Pedestrian Traffic

- 1. Check footwear and remove any loose material before entering Ramp.
- Walk only in designated blue lined walkways.
- 3. Do not cross path of engine exhaust blast or near engine intakes.
- 4. Pick up any stray objects and place in trash container.
- 5. No smoking on Ramp.

b. Vehicular Traffic

All vehicles must be free of Foreign
 Objects (F.O.) material before being
 allowed to enter the Ramp area. This
 requirement will be strictly enforced to
 prevent damage to jet aircraft operating on
 the Ramp.

- Area shown shaded on West Ramp Traffic Plan is restricted to authorized personnel, Ramp support and emergency vehicles.
- 3. Drive only in designated yellow lined roadway.
- 4. Stop at intersections and before going around blind corners.
- 5. Stay clear of fire station doors and fuel pits.
- 6. Do not drive over hoses or cables.
- 7. Drive cautiously when near aircraft.
- 8. Park only in designated areas.
- 9. Due to the potential fire hazard of high temperature generated by a catalytic converter, do not operate a vehicle within 50 feet of any aircraft, fuel truck or trailer, storage or dispensing area, or any potential fire hazard area.

Section III

Safety/Industrial Hygiene

1. Barricades

a. Contractor shall provide signs, barricades, flashing light barricades, and flagging as

11

Contractor Safety/Environmental Awareness

required to keep unauthorized personnel out of the construction area and provide a warning at the job site of any potential hazard.

2. Overhead Work

- a. Barriers must be provided by Contractor to block off areas where MDA personnel could likely walk beneath overhead work. Signs supplied by Contractor must be posted to indicate overhead work in progress.
- b. Where Contractor personnel must work beneath overhead work activities, Contractor shall designate a hard hat area.

3. Housekeeping

 a. Vendor/Contractor employees shall keep work areas clean, neat, and orderly.

4. Ladders

- a. Industrial stepladders shall not exceed
 20 feet. Single ladders or individual rails for extension ladders shall not exceed 30 feet.
- b. Portable metal ladders may not be used for electrical work.
- Ladders shall not be used in front of doorways without posting the area and roping it off.

5. Hoisting

a. Hoisting of suspended loads over any

personnel is prohibited.

- b. MDA overhead hoists shall not be used by Contractor without permission from the MDA Project Manager.
- c. Overhead cranes must be de-energized whenever Contractors must work in close proximity of crane power busses. If work is in the travel path of cranes, but not close to power busses, the crane may be de-energized or isolated by rail stops.

6. Welding

- a. All welding, cutting and open flame operations by the Contractor must be approved by MDA Fire Services prior to commencement. To obtain a Hot Work Permit, contact MDA Fire Services at 232-2285.
- b. Screens or barriers must be set where necessary to protect employees in surrounding areas from the welding flash.

7. Personal Protective Equipment (PPE) and Dress Code

- a. All Contractor employee PPE will be appropriate for the job and supplied by the Contractor.
- b. Contractor personnel assigned to or entering eye protection areas must wear industrial

12

13

— Contractor Safety/Environmental Awareness

safety glasses with industrial safety lenses. Shop areas inside the yellow aisle lines at MDA are mandatory eye protection areas. For jobs where chemical splash hazards exist, goggles, full face shield, or a full face respirator must be worn.

- c. Ordinary sunglasses or light-sensitive lenses are not allowed in eye protection areas unless authorized by the MDA Project Manager.
- d. Ear plugs and/or muffs must be worn in designated areas, or in any location where noise exposure exceeds OSHA limits.
- e. Vendor/Contractor employees assigned to work in the shop, manufacturing, or maintenance areas shall wear sturdy low-heeled (1-1/4 inches max) shoes with closed toe and heel.
- f. Vendor/Contractor employees assigned to work in the shop, manufacturing, or maintenance areas shall wear ankle-length pants and tops that cover the body from the waist up and over the shoulders.
- g. Contractor personnel directly involved with or exposed to moving machinery/tools shall not wear loose-fitting clothing (i.e. skirts, dresses, ties).

8. Hazard Communication

- a. Each Contractor shall make available to
 MDA and other Contractors at the work site a copy of its Hazard Communication
 Program and list of hazardous chemicals, explosives, x-ray or laser equipment that is intended to be used at the site. Each
 Contractor must comply with all aspects of the OSHA Hazard Communication Standard.
- b. Contractors shall supply MDA with copies of the Material Safety Data Sheets (MSDS) for any chemicals requiring an MSDS that they bring on site. The Occupational Safety and Environmental Health Dept. (OSEH) maintains a file of MSDSs for chemicals used at MDA-St. Louis. MSDSs are available for review by contacting the MDA Project Manager. MDA's written Hazard Communication Program and Hazardous Materials List are maintained by OSEH in Bldg. 4.
- c. Containers of hazardous materials used at MDA are identified with a written label and hazard warning. Process tanks are identified with number or letter designations. Tank contents and hazard warnings are posted and correspond to the number/letter designator on the process tank.
- d. Contractor may bring onto MDA premises only the minimum amount of hazardous

materials necessary to do the job. Chemicals and gases must be labeled and stored according to OSHA requirements and in compatible, sturdy, closed containers.

- e. Flammables must be kept in closed metal containers and away from possible ignition sources.
- f. All gas cylinders must be staged in the upright position, secured to prevent falling, with the valve guard in place (if so equipped).

9. Confined Spaces

- a. If Contractor will be performing work in a confined space, the MDA Project Manager must be contacted 48 hours in advance of the entry to obtain any available information regarding the confined space. Compliance with confined space entry requirements is the responsibility of the Contractor.
- Monitoring and ventilation equipment appropriate for the conditions in the confined space must be provided by the Contractor.
- c. A confined space standby person must be provided by the Contractor in accordance with the Confined Space Regulation, 29 CFR 1910.146.

10. Lockout/Tagout

a. All equipment which would present a hazard from inadvertent activation during maintenance or servicing must have the power locked and/ or tagged out except where power is needed to troubleshoot or service equipment.

11. Asbestos

- a. MDA considers all insulation on thermal barriers, troweled on or sprayed-on surfacing and asphalt or vinyl flooring manufactured prior to 1980 to contain asbestos. When activities require either damaging or incidental contact with these Presumed Asbestos Containing Materials (PACM) or other known or suspect asbestos material, contact the MDA Project Manager for specific instruction regarding these materials before proceeding.
- b. If unanticipated PACM is found and incidental contact becomes apparent, the Contractor shall cease work and contact the MDA Project Manager.
- c. In the event of an emergency situation involving a release of asbestos fibers, Contractor shall immediately vacate the areas, call 9-1-1, and provide the dispatcher with any information the Contractor may have. Contractor shall then contact the MDA Project Manager.

16

- d. For work which involves ceiling and the ceiling space, the Contractor shall contact the MDA Project Manager for any additional safety requirements.
- e. Asbestos projects require a 20-day regulatory notification and issuance of a permit before work can begin. Work practices to be used and any deviations from standard work practices must be approved by MDA before this notification form is submitted. Contact the MDA Project Manager to coordinate the work.
- f. Collection of samples to determine the presence of asbestos must be performed by a Certified Asbestos Inspector. Contact the MDA Project Manager to coordinate with OSEH and Environmental and Hazardous Materials Services (EHMS).

Section IV

Environmental Protection

1. General

- a. All contact with environmental regulatory agencies will be coordinated through MDA EHMS.
- b. All hazardous materials (including fuels/oils) will be stored/contained in a manner to prevent accidental discharge/release.

18

Incompatible materials will be stored/ contained a safe distance from each other.

c. Disconnecting or interruption of environmental controls and equipment (pH/ORP probes, tank monitoring systems, flow measurement) must be coordinated with MDA. Contact the MDA Project Manager to coordinate with EHMS.

2. Air Emissions

 a. Any project which will result in the release of dusts, vapors, fumes or other emissions shall be approved by MDA prior to commencement.

3. Waste Management

a. General

- Contractor shall not bring any waste onto MDA property.
- 2. Contractor shall not abandon waste or place it in or near MDA storage facilities without following proper procedures.

b. Hazardous Waste

- For any project which will generate hazardous waste or waste requiring special handling, MDA will arrange/provide for proper disposal, containers, labels, or technical assistance.
- 2. Contractor is responsible for ensuring that all project-generated hazardous waste is

19

Contractor Safety/Environmental Awarenes

handled/stored properly on the job site.

c. Non-Hazardous Solid Waste

- Disposal of non-hazardous solid wastes and demolition debris shall be the responsibility of the Contractor. Contractorgenerated solid waste shall not be placed in any MDA container.
- Non-hazardous waste generated by the Contractor shall not be left on site at the conclusion of a project.

4. Wastewater Discharges

- a. Contractor shall not discharge any material to MDA storm sewer(s).
- b. Contractor shall not use sanitary or industrial sewers for disposal without consent of MDA.

5. Potable Water

- a. Contractor shall not engage in activities which would result in cross contamination or other degradation of the drinking/potable water supply.
- b. Contractor shall use backflow prevention devices as necessary.

Section V

Fire Prevention

- Good housekeeping is an important part of fire prevention. Vendor/Contractor shall keep work areas clean and dispose of smoking material only in approved containers. Trash will not be allowed to remain in any building overnight.
- Contractor shall not store materials and equipment where they obstruct access to firefighting equipment, electrical control panels, ladders, safety showers, or emergency stop devices.
- Contractor shall keep aisles, fire lanes, and exits clear at all times. Contractor shall become familiar with emergency exits in the area in which Contractor is working.
- 4. Contractor shall not tamper with fire extinguishers or alarms.
- Only proper explosion rated or intrinsically safe electrical equipment may be used in areas such as flight hangars and paint booths where explosion proof electrical systems are required.
- 6. Sprinkler and Fire Main Impairments:
 - a. Sprinkler and Fire Main impairments require the approval of MDA Fire Services. 24 hour

20

2.

- advance notification is required for scheduling purposes.
- No work shall be performed that will interfere with the water supply, without first notifying MDA Fire Services for approval.
- c. Only MDA Fire Services representatives shall operate fire main and sprinkler control valves.
- Shoes which are equipped with metal toe and/or heel plates shall not be worn in flammable vapor areas (paint booths, flight hangars, fuel pit areas, etc.).
- 8. Prior to the removal or relocation of any Fire Services alarm wiring or equipment, Contractor shall contact the MDA Project Manager.

Section VI

Security/Site Access

1. Badging


Access to the job site will be through the MDA gate. Vendor/Contractor personnel shall be required to obtain MDA security identification badges and wear them while on MDA premises. Badges will be furnished by MDA Security Department. Vendor/Contractor personnel shall

be restricted to the appropriate work areas, restrooms and cafeterias.

2. Badge Return

Vendor/Contractor employees are responsible for returning MDA identification badges to MDA Security Department upon completion of the contract. There is a fee for lost or non-returned badges. Vendor/Contractor will be held responsible for immediately notifying MDA Security Department in the event of the dismissal and/or termination of an employee possessing a MDA identification badge prior to completion of the job.

Section VII
Visitor Guide Maps
Tract I



Contractor Safety/Environmental Awareness

Contractor Safety/Environmental Awareness


TRACT II WEST

BENEAU FOR THE STATE OF THE S

26 27

Contractor Safety/Environmental Awareness — — — — — — — — — — — Contractor Safety/Environmental Awareness


Tract II North



28


Contractor Safety/Environmental Awareness

Tract IV




29

=Contractor Safety/Environmental Awareness



Tract V



32
Contractor Safety/Environmental Awareness

Section VIII

Vendor/Contractor Safety/ Environmental Awareness Guide

Complete, tear out and give to Security Representative for mailing.

Receipt

I ha	ve received and read the N	ADA Vendori	Comme
tor	Safety/Environment	- VERLOUT	contrac-
	Safety/Environmental	Awareness	Guide.

Name (Print)______

Signed ______

Date ______

Company____

Project/Bldg_____

33

Contractor Safety/Environmental Awareness

NOTES: 35 Contractor Safety/Environmental Awareness

34

Contractor Safety/Environmental Awareness

NOTES:	
	-
	-

36

Contractor Safety/Environmental Awareness =

Appendix H

Report of Occupational Accident, Injury or Illness



REPORT OF OCCUPATIONAL ACCIDENT, INJURY, OR ILLNESS

OFFICE & DEPARTMENT			DEPT. NO.	CENT	ER NO.	DATE OF REPO	RT
			INITIAL REP	ORT		0	
Last Name	First Name	Initiai	Home Address	(Street, Cit	y, State, Zip Code)	•	8
Sex	Employee No.	Social Security No.	Birth	Date		Occupation(Job 1	litle)
Date of Acciden	Time of Accident		Exact Location	of Accident		Did Accident Occ	
Employee's Hon	ne Office & Dept. No.	Result of Accident	(Check All That	Apply):	□Near Miss	□Injury	□lliness
Project No.	8	Supervisor Name			Projec	t Manager Name	
What was emplo	byee doing at time of ac	ccident? (<i>Be specific</i> .	Include informa	tion on took	s, equipment, mater	ials in use and what e	mployee wa
How did the acc	sident occur?*						
		INJURY	/ILLNESS INI	ORMAT	ION		
Type of Injury or	r Iliness.			Part(s)	of Body Affected (Be Specific!)	
Object or Substr	ance Responsible for I	njury/Illness		Date o	f Injury or Initial Dia	gnosis of Illness	
Name and Addr	ess of Treating Physic	ian		Date T	reated	Did Employee Did	□NO dmitted to
Treatment Rece	ived (Be Specific!)					Hospital?	□NO
Name and Addr	ess of Hospital			Date T	reated		
		· · · · · · · · · · · · · · · · · · ·				<u> </u>	
Treatment Rece	ived (Be Specific!)						
Reported By		Title		16	Phone	No.	

*Attach Additional Sheets as Necessary

	. AN	ALYSIS RESULTS	
Detailed description of the accided	nt. State clearly how it happ	pened. Attach separate	sheet and photographs/diagrams as appropriate.
		•	
Who Was in Charge of Work?			t Instructions Given?
Vitnesses*	Years Employee Has with ESE	Years on Present Job	Amount of Experience with Task Being Performed
Proper Protective Tools IIY & Equipment in Use? IN What Hazardous Condition(s) Con	0	xplain Each.* (See Su	ggestions Below)
What Unsafe Act(s) Caused/Cont	ributed to the Accident? Ex	plain Each.* (See Sugg	gestions Below)
Involved Employee's Recommen	dation(s) To Prevent a Simil	ar Occurrence.*	2
mores Employee e i testimine.			
	=1		Si Si
What Action(s) Will Be Taken To	Prevent a Similar Occurren	ce? Be Specific."	
Discussed With Employee By	Date	Involved Empl	oyee's Immediate Supervisor's Signature
Report Approved By			
Employee Comments*			
Employee Signature			Date
HAZARDOUS CONDITIONS Concested area-	Poor housekeeping Slick surface		Improper use of hands or body parts Improper use of tools/equipment
insufficient workspace	Special task sesignment		Instantion
Defective apparel Defective equipment	No hazardous condition		Inexperience Lack of communication
Environmental factor	UNSAFE ACTS		Lack of knowledge/skills
Improper apparel	Disregard of Instructions		Lack of proper equipment/tools
Improper design Improper equipment	Disregard of eafety rules Due to vehicular acciden		Oversetimation of personal capability Poor judgement
Improper Munication	Failure to use/improper u		Unsafe loading, pulling or mixing
improper ventilation	protective equipment		Uneste rigging
Improperty guerded Inclement weather	Horseplay Improper lifting method		Unante speed Using defective equipment
Lack of proper tools/equipment	Improper positioning of a	oolf	Working on moving equipment
Obscured vision	Improper operating meth		No unsafe act